



Cadmium Ion Sensors



ELECTRO-CHEMICAL DEVICES

Features

- Model S80 Universal Style Sensors
- Multiple materials of construction
- Integral Signal Conditioner
- Replaceable Electrode Cartridge
- Dual Channel Analyzers, pH/pION, pION/pION

Benefits

- Insertion, Immersion or Valve Retractable Service
- 316 Stainless Steel, Titanium, Hastelloy
- Noise free transmission
- Simple and Economical Service
- Mix and Match your choice of measurements



Model S80 Sensors
Cadmium Ion Sensors

Description

The Model S80 universal sensors provide a stable and economical platform for the in line measurement of pH, ORP, Specific Ion, Dissolved Oxygen, Conductivity or Resistivity. The Model S80 is an insertion or immersion style sensor for use in pipe Tees or on the end of a Stand Pipe for immersion into a tank or pond. The Model S80 is also available as a valve retractable design allowing insertion or removal of the sensor into a pipe without interrupting the process flow. Both sensor designs use easily replaceable electrode cartridges. ECD offers several ion selective electrode cartridges suitable for continuous online measurement.

The Cadmium Ion Electrode is a combination electrode with a cadmium sulfide (CdS) solid state pressed crystal sensing element and a double junction reference electrode. The cadmium Ion Selective Electrode cartridge develops a millivolt potential proportional to the concentration of free cadmium ions, Cd^{+2} , in the measured solution. The typical output is 25mV to 30mV per decade of change in concentration. The speed of response varies from a few seconds in concentrated solutions up to a few minutes in the lower ppm ranges. The Cadmium Ion sensors are used with the Model T80 Transmitter with its dual channel mix and match capabilities. This analyzer will measure cadmium ions from 0.1 ppm to 11,200 ppm autoranging the display between the ppb, ppm and ppt (parts per thousand) scales.

The cadmium ion electrode is poisoned by copper, silver, lead, ferric and mercury ions in solution. Copper, silver and mercury must be absent from the measured solution. Ferric and Lead must be at a lower concentration than the cadmium. Polishing the sensor with the supplied polishing strips will restore the function if the sensing tip becomes poisoned.

In basic solutions, cadmium reacts with hydroxide and precipitates as $Cd(OH)_2$, cadmium hydroxide is not measured by the sensor. The Hydrogen ion (the pH) interferes with the cadmium measurement at low ppm levels, limiting the pH range to values greater than pH3 and less than pH9.

The sensor is calibrated using two standard solutions differing in concentration by a factor of 10, i.e. 10 ppm and 100 ppm. The calibration sets the slope of the electrode, mV/decade, and the zero potential for the sensor.

In many cases the process solution's ionic strength, temperature and pH value will differ widely from the calibration solution. These factors will affect the zero potential of the cadmium sensor causing an offset. To eliminate the offset perform a standardization, a single point in-line calibration. Once the sensor has stabilized in the process, take a grab sample and determine the Cd^{+2} value. Adjust the analyzer to read this laboratory determined value, verify weekly.

Cadmium Ion Sensors

Specifications

Model S80 Sensors

Combination electrode cartridge with a cadmium sulfide sensing cell and a double junction, $\text{KNO}_3/\text{KCl}/\text{AgCl}$, reference electrode, signal conditioner, ATC

Electrode Slope

27 ± 3 mV per decade of concentration change

Measurement Range

Cadmium ion: 0.1 ppm to 11,200 ppm (3-9 pH)
 10^{-7} molar to 0.1 molar

Temperature Range

0° C to 80° C (32° F to 176° F)

Pressure Range

0 - 50 psig (0 - 3.5 barg)

Response Time

T90 in 10 seconds

Electrode Life

6 to 12 months

Interfering ions

Copper, Silver, Mercury, Lead, Ferric must be absent

Wetted Materials

Radel, epoxy, CdS, PTFE, 316 SS, Viton O-Ring

Process Connections

S80 Insertion: $\frac{3}{4}$ " MNPT compression fitting

S80 Valve Retractable: 1" MNPT Ball Valve

Model T80 Transmitter

General purpose, $\frac{1}{2}$ DIN, NEMA 4X, 110/220 VAC, 24 VDC or 4-20 mA loop powered, CE Marking, single or dual channel, (1) or (2) 4-20 mA outputs, optional (3) Alarm Relays 250 VAC 3 amp, MODBUS RTU (standard) or HART 7, Auto ranging display, ppb → ppm → ppthousand

| Part No. | Model and Product Description |
|----------------------|--|
| S80-00-0002-0100-073 | S80 Cadmium, Cd^{+2} insertion style sensor with $\frac{3}{4}$ " 316 SS compression fitting, 316 SS body, $\frac{3}{4}$ " Diameter. x 10" length, 10 ft cable |
| S80-00-0002-0300-073 | S80 Cadmium, Cd^{+2} insertion style sensor with $\frac{3}{4}$ " 316 SS compression fitting, 316 SS body, $\frac{3}{4}$ " Diameter. x 10" length, 30 ft cable |
| S80-01-0131-0110-073 | S80 Cadmium, Cd^{+2} Valve Retractable Style with 1" Ball Valve Assembly, 316 SS body, $\frac{3}{4}$ " Diameter x 17" length, 10 ft cable |
| S80-01-0131-0310-073 | S80 Cadmium, Cd^{+2} Valve Retractable Style with 1" Ball Valve Assembly, 316 SS body, $\frac{3}{4}$ " Diameter x 17" length, 30 ft cable |
| T80-10-21-00-1 | Model T80 Single Channel Transmitterr, 110/220 VAC, (1) 4-20 mA outputs, (3) Alarm Relays, UM |
| T80-11-21-20-1 | Model T80 Dual Channel Transmitterr, 110/220 VAC, (2) 4-20 mA outputs, (3) Alarm Relays, UM |

| Part No. | Spare Parts and Accessories Description |
|-------------|---|
| 2005140.VIT | Cadmium Ion Electrode, Radel body, double junction Teflon Ref, 0.1 ppm -11,200 ppm, 0°-80°C |
| 2010468 | Cadmium Ion Calibration Solution, 10 ppm, 500 ml |
| 2010469 | Cadmium Ion Calibration Solution, 100 ppm, 500 ml |
| 2000250-1 | Polishing Strip Kit, abrasive cleaning strips for Ion electrodes |
| | |

Specifications subject to change without notice.

Represented by:

Electro-Chemical Devices

1681 Kettering

Irvine, California, USA 92614

Phone: +1-949-336-6060

+1-800-729-1333

Fax: +1-949-336-6064

email: sales@ecdi.com

web: www.ecdi.com

