

MODEL CA6 - IRON ANALYZER

Compact online colorimeter for the automatic measurement of Iron

APPLICATION FIELDS

- Drinking water
- Iron removal processes and residual coagulant monitoring
- Industrial wastewater
- Measurement of effluents and wastewaters
- Boiler feed water
- Corrosion control
- Cooling water
- Surface water



ADVANTAGES / FEATURES

Dual compartment enclosure

To ensure complete separation between the electronics and the wet part.

One reagent configuration, low reagent consumption

Minimum operating cost by small reagent consumption, only 2.5L (0.66 US.gal) for the 16 mm cell / 5L (1.32 US.gal) for the 26 mm cell of each reagent every 60 days with 15 minute analysis frequency. Very long shelf life of the reagent.

Automatic calibration / validation / cleaning

Validation, cleaning and calibration are standard features which significantly reduce downtime and operator intervention ensuring the most accurate results are obtained.

Free selectable validation, cleaning and calibration intervals.

Wide measuring range

The determination ranges of the CA6 Iron Analyzer vary from trace µg/L to 10 mg/L using internal dilution module.

Color touchscreen user interface


The CA6 Colorimeter is equipped with a graphic touchscreen interface showing measured values and status information. Easy access to menus and functions. Multiple languages. Integrated datalogger with USB download.

Factory tested, ready for installation and operation

Just connect the power, sample, and reagent lines and the analyzer is fully operational.

Multiple streams

Dual streams version available. External Sequencer, switching up to 4 sample streams.



MEASUREMENT PRINCIPLE In an acid buffered solution, ferrozine and iron react to form a purple colored complex measured at 572 nm. The absorption intensity is proportional to the iron concentration in the sample.

TECHNICAL SPECIFICATIONS

Measured parameter:	Fe ²⁺ , Fe ³⁺ , Total Dissolved Iron (ppb, ppm, mg/l).	Dimensions (H x W x D):	23.6 x 15.0 x 8.2 in / 606 x 380 x 209 mm
Measuring principle:	Differential photometric absorbance.	Weight:	Approx. 44 lbs (20 Kg)
Measuring range:	2 to 250 ppb (26 mm cell) 9 to 500 ppb (16 mm cell) up to 10 mg/L with internal dilution.	Power supply:	Voltage: 100 - 240 VAC 50/60 Hz standard or 24 VDC (option) Power consumption: max. 80 VA
Reproducibility:	± 1 ppb or ± 5%, whichever is greater (26 mm cell) ± 5 ppb or ± 5%, whichever is greater (16 mm cell)	Outputs:	2 x 4-20 mA outputs for measured data Modbus RTU RS485
Analysis frequency:	Freely programmable, batch near-continuous analysis.	Alarms:	4 SPDT programmable potential free relays
Cycle time:	8-10 minutes, including conditioning before analysis cycle and rinsing after measuring.	Digital input:	Remote start / stop
Reaction cell:	Temperature heated	Operating Temperature:	41 - 113 °F (5 - 45 °C)
Sample:	Pressure-free from overflow vessel Temperature: 41 - 122 °F (5 to 50 °C) Flow Rate: 80 to 500 mL/min Connection: 6 mm (¼-in.)	Humidity:	10 to 90% non-condensing (indoor use, outdoor installation only possible with protective cabinet or shelter not included)
Drain:	Pressure-free, atmospheric drain Connection: 12 mm (½-in.)	Installation:	Wall mount (standard), bench top support or panel mount (options).
N° of streams:	1, 2 with integrated switching valve 3, 4 with external sequencer	Ingress Protection:	IP54

